



BALL VALVES CHECK VALVES



VANNES À BILLE - CLAPETS DE RETENUE



ШАРОВЫЕ И ОБРАТНЫЕ КЛАПАНЫ




SUPAPE CU BILĂ - SUPAPA DE RETINERE



VÁLVULAS DE ESFERA - VÁLVULAS
ANTIRETORNO



KUGELVENTILE - RÜCKSCHLAGVENTILE



Code Code APT. Cod Código Kode	Page Page CTR. Página Página Seite
20.04.00	1.15
20.05.00	1.15
2093.15.00	1.13
2093.15.20	1.13
2093.22.00	1.13
2093.22.20	1.13
2093.28.00	1.13
2093.28.20	1.13
2093.35.00	1.13
2093.35.20	1.13
2093.42.20	1.13
2093.54.20	1.13
24.32.10	1.15
2544.05.00	1.11
2544.05.10	1.11
2544.22.00	1.12
2544.22.10	1.12
2860.04.02	1.05
2860.04.12	1.05
2860.05.02	1.05
2860.05.12	1.05
2959.03.00	1.02
2959.03.70	1.02
2959.03.90	1.02
2959.04.00	1.02
2959.04.70	1.02
2959.04.90	1.02
2959.05.00	1.02
2959.05.70	1.02
2959.05.90	1.02
2959.06.00	1.02
2959.06.70	1.02
2959.06.90	1.02
2959.07.00	1.02
2959.07.70	1.02
2959.07.90	1.02
2959.08.00	1.02
2959.08.90	1.02
2959.09.00	1.02
2959.09.90	1.02
2960.03.00	1.03
2960.03.70	1.03
2960.03.90	1.03
2960.04.00	1.03
2960.04.70	1.03
2960.04.90	1.03
2960.05.00	1.03
2960.05.70	1.03
2960.05.90	1.03
2960.06.00	1.03
2960.06.70	1.03
2960.06.90	1.03
2960.07.00	1.03
2960.07.70	1.03
2960.07.90	1.03
2960.08.00	1.03
2960.08.90	1.03
2960.09.00	1.03
2960.09.90	1.03
3082 22	1.14
3082 30	1.14
3082 40	1.14
3085 02I	1.14
3085 04I	1.14
3085 10I	1.14
3085 12I	1.14
3085 20I	1.14
3085 34I	1.14
3085 38I	1.14
3086 02I	1.14
3086 04I	1.14
3086 10I	1.14
3086 12I	1.14
3086 20I	1.14
3086 22	1.14
3086 30	1.14
3086 34I	1.14
3086 38I	1.14
3086 40	1.14
3171.04.00	1.06

Code Code APT. Cod Código Kode	Page Page CTP. Pagina Página Seite
3171.05.00	1.06
3171.06.00	1.06
3172.04.00	1.06
3172.05.00	1.06
3172.06.00	1.06
3176.05.00	1.06
3176.06.00	1.06
3255 10NI	1.01
3255 12NI	1.01
3255 34NI	1.01
3256 10NI	1.01
3256 12NI	1.01
3256 34NI	1.01
3346.04.70	1.04
3346.05.70	1.04
3346.06.70	1.04
3346.07.70	1.04
3371 02NI	1.00
3371 04NI	1.00
3371 10NI	1.00
3371 12NI	1.00
3371 14NI	1.00
3371 20NI	1.00
3371 22N	1.00
3371 22N	1.02
3371 22N	1.07
3371 30N	1.00
3371 30N	1.02
3371 30N	1.07
3371 34NI	1.00
3371 38NI	1.00
3371 40N	1.00
3371 40N	1.02
3371 40N	1.07
3372 04NI	1.00
3372 10NI	1.00
3372 12NI	1.00
3372 14NI	1.00
3372 34NI	1.00
3372 38NI	1.00
3373 02NI	1.00
3373 04NI	1.00
3373 10NI	1.00
3373 12NI	1.00
3373 14NI	1.00
3373 20NI	1.00
3373 34NI	1.00
3373 38NI	1.00
3374 10NI	1.01
3374 12NI	1.01
3374 14NI	1.01
3374 34NI	1.01
3374 38NI	1.01
3386 09NI	1.01
3386 A1NI	1.01
3386 A2NI	1.01
3465.04.00	1.13
3465.05.00	1.13
3465.06.00	1.13
589.05.00	1.15
589.06.00	1.15
67.04.02	1.10
67.04.12	1.10
67.05.02	1.10
67.05.12	1.10
67.06.02	1.10
67.06.12	1.10
67.06.80	1.04
67.06.90	1.04
67.07.02	1.10
67.07.12	1.10
854.04.32	1.07
854.04.42	1.07
854.05.32	1.07
854.05.42	1.07
854.06.32	1.07
854.06.42	1.07
854.07.32	1.07
854.07.42	1.07
854.08.32	1.07

[illegible][illegible][illegible]

BALL VALVES CHECK VALVES

-  VANNES À BILLE - CLAPETS DE RETENUE
-  ШАРОВЫЕ И ОБРАТНЫЕ КЛАПАНЫ
-  SUPAPE CU BILĂ - SUPAPA DE RETINERE
-  VÁLVULAS DE ESFERA - VÁLVULAS ANTIRETORNO
-  KUGELVENTILE - RÜCKSCHLAGVENTILE



Water ball valves
- GS ARNO heavy full bore range



Water ball valves
- RBM NILO full bore range



Water ball valves
- RBM IRO standard bore range



Check valves



Accessories



3371

Heavy full bore ball valve, lever handle operated, FF connections.

Suitable for water, water+ glycol, steam, hydrocarbons.

Nickel plated brass body.

Thick chrome plated brass ball.

PTFE seal.

Threaded connections UNI-EN-ISO 228.

- Operating temperature with water -20 ÷ 120 °C



- PED



047

Heavy full bore ball valve, lever handle operated, FF connections

Vanne à bille passage intégral série lourde, actionnement par poignée à levier, raccords FF

Усиленный полнопроходной шаровый кран с ручкой-рычагом, вн.- вн. резьба

Supapă cu bilă cu trecere totală debit masiv, cu acționare cu manetă tip levier, prinderi Mamă/Mamă

Válvula de esfera hembra-hembra con palanca en aluminio, paso total, pesante

Kugelventil schwerer Volldurchfluss, Betätigung mit Hebelgriff, Anschlüsse FF

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN PN	EURO EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Коп. Ambalaj Embalaje Verpack.
3371 14NI	1/4"	40	-	10	160
3371 38NI	3/8"	40	-	10	160
3371 12NI	1/2"	40	-	8	64
3371 34NI	3/4"	40	-	6	48
3371 10NI	1"	40	-	6	48
3371 04NI	1"1/4 *	40	-	4	32
3371 02NI	1"1/2 *	40	-	2	16
3371 20NI	2" *	40	-	2	10
3371 22N	2"1/2 *	25	-	8	8
3371 30N	3" *	25	-	6	6
3371 40N	4" *	10	-	4	4

3372

Heavy full bore ball valve, butterfly handle operated, FF connections.

Suitable for water, water+ glycol, steam, hydrocarbons.

Nickel plated brass body.

Thick chrome plated brass ball.

PTFE seal.

Threaded connections UNI-EN-ISO 228.

- Operating temperature with water -20 ÷ +120 °C



- PED



047

Heavy full bore ball valve, butterfly handle operated, FF connections

Vanne à bille passage intégral série lourde, actionnement par poignée papillon, raccords FF

Усиленный полнопроходной шаровый кран с ручкой-бабочкой, вн.- вн. резьба

Supapă cu bilă cu trecere totală debit masiv, cu acționare cu manetă tip fluture, prinderi Mamă/Mamă

Válvula de esfera hembra-hembra con palomilla en aluminio, paso total, pesante

Kugelventil schwerer Volldurchfluss, Betätigung mit Flügelgriff, Anschlüsse FF

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN PN	EURO EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Коп. Ambalaj Embalaje Verpack.
3372 14NI	1/4"	40	-	10	160
3372 38NI	3/8"	40	-	10	160
3372 12NI	1/2"	40	-	10	120
3372 34NI	3/4"	40	-	5	80
3372 10NI	1"	40	-	5	60
3372 04NI	1"1/4 *	40	-	4	32

3373

Heavy full bore ball valve, lever handle operated, MF connections.

Suitable for water, water+ glycol, steam, hydrocarbons.

Nickel plated brass body.

Thick chrome plated brass ball.

PTFE seal.

Threaded connections UNI-EN-ISO-228.

- Operating temperature with water -20 ÷ 120 °C



- PED



047

Heavy full bore ball valve, lever handle operated, MF connections

Vanne à bille passage intégral série lourde, actionnement par poignée à levier, raccords MF

Усиленный полнопроходной шаровый кран с ручкой-рычагом, нар.- вн. резьба

Supapă cu bilă cu trecere totală debit masiv, cu acționare cu manetă tip levier, prinderi Tată/Mamă

Válvula de esfera macho-hembra con palanca en aluminio, paso total, pesante

Kugelventil schwerer Volldurchfluss, Betätigung mit Hebelgriff, Anschlüsse MF

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN PN	EURO EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Коп. Ambalaj Embalaje Verpack.
3373 14NI	1/4"	40	-	10	160
3373 38NI	3/8"	40	-	10	160
3373 12NI	1/2"	40	-	10	120
3373 34NI	3/4"	40	-	6	48
3373 10NI	1"	40	-	4	48
3373 04NI	1"1/4 *	40	-	4	32
3373 02NI	1"1/2 *	40	-	2	20
3373 20NI	2" *	40	-	2	10

3374

Heavy full bore ball valve, butterfly handle operated, MF connections. Suitable for water, water+ glycol, steam, hydrocarbons.

Nickel plated brass body.
Thick chrome plated brass ball.
PTFE seal.
Threaded connections UNI-EN-ISO 228.

- Operating temperature with water -20 ÷ 120 °C



- Heavy full bore ball valve, butterfly handle operated, MF connections
- Vanne à bille passage intégral série lourde, actionnement par poignée papillon, raccords MF
- Усиленный полнопроходной шаровый кран с ручкой-бабочкой нар.- вн. резьба
- Supapă cu bilă cu trecere totală debit masiv, cu acționare cu manetă tip fluture, prinderi Tată/Mamă
- Válvula de esfera macho-hembra con palomilla en aluminio, paso total, pesante
- Kugelventil schwerer Volldurchfluss, Betätigung mit Flügelgriff, Anschlüsse MF

Code Code Articul Cod Codigo Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN	EURO EURO EURO EURO EURO	Pack Cond. Ynak. Cutie Caja Pack.	Carton Emballage Kop. Ambalaj Embalaje Verpack.
3374 14NI	1/4"	40	-	10	160
3374 38NI	3/8"	40	-	10	160
3374 12NI	1/2"	40	-	10	120
3374 34NI	3/4"	40	-	5	60
3374 10NI	1"	40	-	5	60

3386

Heavy full bore angle ball valve, butterfly handle operated, F connection with M inlet coupling. Suitable for water, water+ glycol, steam, hydrocarbons.

Nickel plated brass body.
Thick chrome plated brass ball.
PTFE seal.
Threaded connections UNI-EN-ISO 228.

- Operating temperature with water -20 ÷ 120 °C



- Heavy full bore angle ball valve, butterfly handle operated, F connection with M inlet coupling
- Vanne à bille en équerre passage intégral série lourde, actionnement par poignée papillon, raccord F avec manchon M
- Усиленный, полнопроходной, угловой шаровой кран с ручкой-бабочкой, вн. резьба - американка с наружной резьбой
- Supapă cu bilă în echer cu trecere totală debit masiv, cu acționare cu manetă tip fluture, prindere tip Mamă, cu ștuț tip Tată
- Válvula de esfera escuadra macho-hembra con racor 3 piezas, con palomilla en aluminio, paso total, pesante
- Quadratisches Kugelventil schwerer Volldurchfluss, Betätigung mit Flügelgriff, Anschluss F mit M-Stutzen

Code Code Articul Cod Codigo Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN	EURO EURO EURO EURO EURO	Pack Cond. Ynak. Cutie Caja Pack.	Carton Emballage Kop. Ambalaj Embalaje Verpack.
3386 09NI	1/2" x 1/2"	40	-	10	120
3386 A1NI	3/4" x 3/4"	40	-	5	60
3386 A2NI	1" x 1"	40	-	4	40

3255

Ball bib-cock, lever handle operated. Suitable for water, water+ glycol, steam, hydrocarbons.

Nickel plated brass body.
Thick chrome plated brass ball.
PTFE seal.
Elastomer OR gaskets.
Threaded connections UNI-EN-ISO 228.

- Operating temperature with water -20 ÷ 120 °C



- Ball bib-cock, with lever handle
- Robinet de distribution coudé à bille, avec poignée à levier
- Шаровый кран с изогнутым сливом и с ручкой-рычагом
- Robinet de distribuție curbat cu bilă, cu manetă de tip levier
- Grifo de jardín con palanca en aluminio, con toma para manguera
- Gekrümmter Kugelhahn mit Hebelgriff

Code Code Articul Cod Codigo Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN	EURO EURO EURO EURO EURO	Pack Cond. Ynak. Cutie Caja Pack.	Carton Emballage Kop. Ambalaj Embalaje Verpack.
3255 12NI	1/2"	30	-	10	80
3255 34NI	3/4"	30	-	5	50
3255 10NI	1"	30	-	4	20

3256

Ball bib-cock, butterfly handle operated. Suitable for water, water+ glycol, steam, hydrocarbons.

Nickel plated brass body.
Thick chrome plated brass ball.
PTFE seal.
Elastomer OR gaskets.
Threaded connections UNI-EN-ISO 228.

- Operating temperature with water -20 ÷ 120 °C



- Ball bib-cock, with butterfly handle
- Robinet de distribution coudé à bille, avec poignée papillon
- Шаровый кран с изогнутым сливом и с ручкой-бабочкой
- Robinet de distribuție curbat cu bilă, cu manetă de tip fluture
- Grifo de jardín con palomilla en aluminio, con toma para manguera
- Gekrümmter Kugelhahn mit Flügelgriff

Code Code Articul Cod Codigo Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN	EURO EURO EURO EURO EURO	Pack Cond. Ynak. Cutie Caja Pack.	Carton Emballage Kop. Ambalaj Embalaje Verpack.
3256 12NI	1/2"	30	-	10	80
3256 34NI	3/4"	30	-	5	50
3256 10NI	1"	30	-	4	20

2959

Full bore ball valve, lever handle operated, FF connections. Suitable for water, water+glycol.

Nickel brass body.
Chromed brass valve with thickness.
PTFE seal.
Elastomer OR gasket.
Threaded connections ISO 7 (UNI EN 10226).

- Operating temperature with water -20 ÷ +120 °C (without steam)



- Full bore ball valve, lever handle operated, FF connections
- Vanne à bille passage intégral, actionnement par poignée à levier, raccords FF*
- Полнопроходной шаровый кран с ручкой-рычагом, вн.- вн. резьба
- Supară cu bilă cu trecere totală, cu acționare cu manetă tip levier, prinderi Mamă/Mamă*
- Válvula de esfera hembra-hembra con palanca en aluminio, paso total*
- Kugelventil Volldurchfluss, Betätigung mit Hebelgriff, Anschlüsse FF*

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN PN	EURO EURO EURO EURO EURO EURO	Pack Cond. Ynak. Cutie Caja Pack.	Carton Emballage Kop. Ambalaj Embalaje Verpack.
2959.03.90	3/8"	50	-	10	40
2959.04.90	1/2"	40	-	10	80
2959.05.90	3/4"	40	-	5	50
2959.06.90	1"	40	-	4	40
2959.07.90	1 1/4"	30	-	4	24
2959.08.90	1 1/2"	25	-	2	12
2959.09.90	2"	25	-	2	8
3371 22N	2 1/2"	25	-	8	8
3371 30N	3"	25	-	6	6
3371 40N	4"	10	-	4	4

052



ISO 7 (UNI EN 10226) threaded connections.

2959

Full bore ball valve, lever handle operated, FF connections. Suitable for water, water+glycol.

Nickel brass body.
Chromed brass valve with thickness.
PTFE seal.
Elastomer OR gasket.
Threaded connections ISO 7 (UNI EN 10226).

- Operating temperature with water -20 ÷ +120 °C (without steam)



- Full bore ball valve, lever handle operated, FF connections
- Vanne à bille passage intégral, actionnement par poignée à levier, raccords FF*
- Полнопроходной шаровый кран с ручкой-рычагом, вн.- вн. резьба
- Supară cu bilă cu trecere totală, cu acționare cu manetă tip levier, prinderi Mamă/Mamă*
- Válvula de esfera hembra-hembra con palanca en aluminio, paso total*
- Kugelventil Volldurchfluss, Betätigung mit Hebelgriff, Anschlüsse FF*

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN PN	EURO EURO EURO EURO EURO EURO	Pack Cond. Ynak. Cutie Caja Pack.	Carton Emballage Kop. Ambalaj Embalaje Verpack.
2959.03.00	3/8"	50	-	10	40
2959.04.00	1/2"	40	-	10	80
2959.05.00	3/4"	40	-	5	50
2959.06.00	1"	40	-	4	40
2959.07.00	1 1/4"	30	-	4	24
2959.08.00	1 1/2"	25	-	2	12
2959.09.00	2"	25	-	2	8

052



ISO 7 (UNI EN 10226) threaded connections.

2959

Full bore ball valve, butterfly handle operated, FF connections. Suitable for water, water+glycol.

Nickel brass body.
Chromed brass valve with thickness.
PTFE seal.
Elastomer OR gasket.
Threaded connections ISO 7 (UNI EN 10226).

- Operating temperature with water -20 ÷ +120 °C (without steam)



- Full bore ball valve, butterfly handle operated, FF connections
- Vanne à bille passage intégral, actionnement par poignée papillon, raccords FF*
- Полнопроходной шаровый кран с ручкой-бабочкой, вн.- вн. резьба
- Supară cu bilă cu trecere totală, cu acționare cu manetă tip fluture, prinderi Mamă/Mamă*
- Válvula de esfera hembra-hembra con palomilla en aluminio, paso total*
- Kugelventil Volldurchfluss, Betätigung mit Flügelgriff, Anschlüsse FF*

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN PN	EURO EURO EURO EURO EURO EURO	Pack Cond. Ynak. Cutie Caja Pack.	Carton Emballage Kop. Ambalaj Embalaje Verpack.
2959.03.70	3/8"	50	-	10	40
2959.04.70	1/2"	40	-	10	80
2959.05.70	3/4"	40	-	5	50
2959.06.70	1"	40	-	5	40
2959.07.70	1 1/4"	30	-	4	24

052



ISO 7 (UNI EN 10226) threaded connections.

2960

Full bore ball valve, lever handle operated, MF connections. Suitable for water, water+glycol.

Nickel brass body.
Chromed brass valve with thickness.
PTFE seal.
Elastomer OR gasket.
Threaded connections ISO 7 (UNI EN 10226).

- Operating temperature with water $-20 \div +120^{\circ}\text{C}$ (without steam)



- Full bore ball valve, lever handle operated, MF connections
- Vanne à bille passage intégral, actionnement par poignée à levier, raccords MF
- Полнопроходной шаровый кран с ручкой-бабочкой, вн.-вн. резьба
- Supară cu bilă cu trecere totală, cu acționare cu manetă tip levier, prinderi Tată/Mamă
- Válvula de esfera macho-hembra con palanca en aluminio, paso total
- Kugelventil Volldurchfluss, Betätigung mit Hebelgriff, Anschlüsse MF

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN PN	EURO EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Kop. Ambalaj Embalaje Verpack.
2960.03.90	3/8"	50	-	10	40
2960.04.90	1/2"	40	-	10	80
2960.05.90	3/4"	40	-	5	50
2960.06.90	1"	40	-	4	40
2960.07.90	1 1/4"	30	-	4	24
2960.08.90	1 1/2"	25	-	2	12
2960.09.90	2"	25	-	2	8

052



ISO 7 (UNI EN 10226) threaded connections.

2960

Full bore ball valve, lever handle operated, MF connections. Suitable for water, water+glycol.

Nickel brass body.
Chromed brass valve with thickness.
PTFE seal.
Elastomer OR gasket.
Threaded connections ISO 7 (UNI EN 10226).

- Operating temperature with water $-20 \div +120^{\circ}\text{C}$ (without steam)



- Full bore ball valve, lever handle operated, MF connections
- Vanne à bille passage intégral, actionnement par poignée à levier, raccords MF
- Полнопроходной шаровый кран с ручкой-бабочкой, вн.-вн. резьба
- Supară cu bilă cu trecere totală, cu acționare cu manetă tip levier, prinderi Tată/Mamă
- Válvula de esfera macho-hembra con palanca en aluminio, paso total
- Kugelventil Volldurchfluss, Betätigung mit Hebelgriff, Anschlüsse MF

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN PN	EURO EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Kop. Ambalaj Embalaje Verpack.
2960.03.00	3/8"	50	-	10	40
2960.04.00	1/2"	40	-	10	80
2960.05.00	3/4"	40	-	5	50
2960.06.00	1"	40	-	4	40
2960.07.00	1 1/4"	30	-	4	24
2960.08.00	1 1/2"	25	-	2	12
2960.09.00	2"	25	-	2	8

052



ISO 7 (UNI EN 10226) threaded connections.

2960

Full bore ball valve, butterfly handle operated, MF connections. Suitable for water, water+glycol.

Nickel brass body.
Chromed brass valve with thickness.
PTFE seal.
Elastomer OR gasket.
Threaded connections ISO 7 (UNI EN 10226).

- Operating temperature with water $-20 \div +120^{\circ}\text{C}$ (without steam)



- Full bore ball valve, butterfly handle operated, MF connections
- Vanne à bille passage intégral, actionnement par poignée papillon, raccords MF
- Полнопроходной шаровый кран с ручкой-бабочкой, нар.-вн. резьба
- Supară cu bilă cu trecere totală, cu acționare cu manetă de tip fluture, prinderi Tată/Mamă
- Válvula de esfera macho-hembra con palomilla en aluminio, paso total
- Kugelventil Volldurchfluss für Gas mit Flügelgriff, Anschlüsse MF

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN PN	EURO EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Kop. Ambalaj Embalaje Verpack.
2960.03.70	3/8"	50	-	10	40
2960.04.70	1/2"	40	-	10	80
2960.05.70	3/4"	40	-	5	50
2960.06.70	1"	40	-	5	40
2960.07.70	1 1/4"	30	-	4	24

052



ISO 7 (UNI EN 10226) threaded connections.

3346

Full bore ball valve, butterfly handle operated, F connection with M inlet coupling. Suitable for water, water+ glycol.

Nickel brass body.
Chromed brass valve with thickness.
PTFE seal.
Elastomer OR gasket.
Threaded connections ISO 7 (UNI EN 10226).

- Operating temperature with water -20 ÷ +120 °C (without steam)



- Full bore ball valve, butterfly handle operated, F connection with M inlet coupling
- Vanne à bille passage intégral, actionnement par poignée papillon, raccord F avec manchon M
- Усиленный полнопроходной шаровый кран с ручкой-бабочкой вн. резьба - американка с наружной резьбой
- Supară cu bilă cu trecere totală debit, cu acționare cu manetă tip fluture, prinderi Mamă, cu ștuț tip Tată
- Válvula de esfera macho-hembra con racor 3 piezas, con palomilla en aluminio, paso total
- Kugelventil schwerer Volldurchfluss, Betätigung mit Flügelgriff, Anschluss F mit M-Stutzen

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN	EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Кор. Ambalaj Embalaje Verpack.
3346.04.70	1/2" x 1/2"	40	-	15	90
3346.05.70	3/4" x 3/4"	40	-	10	40
3346.06.70	1" x 1"	40	-	5	30
3346.07.70	1"1/4 x 1"1/4	30	-	4	16



052



ISO 7 (UNI EN 10226) threaded connections.

67

Full bore ball valve, knob operated complete with immersion thermometer with removable rear bulb, MF connections, with OR seal fitting. Suitable for water, water+glycol.

Nickel plated brass body.
Thick chrome plated brass ball.
PTFE seal.
Elastomer OR gaskets.
Threaded connections UNI-EN-ISO 228.

- Operating temperature with water -20 ÷ +120 °C (without steam)

- Thermometer scale 0 ÷ +80 °C



- Full bore ball valve, knob operated complete with thermometer, MF connections with OR seal fitting
- Vanne à bille passage intégral, actionnement par poignée avec thermomètre, raccords MF avec raccord à joint torique
- Полнопроходной шаровый кран с термометром, нар.- вн. резьба, соединение с уплотнительным кольцом OR
- Supară cu bilă cu trecere totală, acționare prin buton prevăzută cu termometru, prinderi Tată/Mamă cu racor cu garnitură OR
- Válvula de esfera macho-hembra con racor 3 piezas con autojunta, volante rojo con termómetro, paso total
- Kugelventil Volldurchfluss, Betätigung mit Drehknopf komplett mit Thermometer, Anschlüsse MF mit OR-Dichtungsanschluss

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN	EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Кор. Ambalaj Embalaje Verpack.
67.06.90	1"	25	-	2	10



052



Fitting with OR seal connection.

67

Full bore ball valve, knob operated complete with immersion thermometer with removable rear bulb, MF connections, with OR seal fitting. Suitable for water, water+glycol.

Nickel plated brass body.
Thick chrome plated brass ball.
PTFE seal.
Elastomer OR gaskets.
Threaded connections UNI-EN-ISO 228.

- Operating temperature with water -20 ÷ +120 °C (without steam)

- Thermometer scale 0 ÷ +80 °C



- Full bore ball valve, knob operated complete with thermometer, MF connections, with OR seal fitting
- Vanne à bille passage intégral, actionnement par poignée avec thermomètre, raccords MF, avec raccord à joint torique
- Полнопроходной шаровый кран с термометром, нар.- вн. резьба, соединение с уплотнительным кольцом OR
- Supară cu bilă cu trecere totală, acționare prin buton prevăzută cu termometru, prinderi Tată/Mamă, cu racor cu garnitură OR
- Válvula de esfera macho-hembra con racor 3 piezas con autojunta, volante azul con termómetro, paso total
- Kugelventil Volldurchfluss, Betätigung mit Drehknopf komplett mit Thermometer, Anschlüsse MF mit OR-Dichtungsanschluss

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN	EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Кор. Ambalaj Embalaje Verpack.
67.06.80	1"	25	-	2	10



052



Fitting with OR seal connection.

2860

Ball bib-cock, with lever handle. Suitable for water, water+glycol.

Nickel plated brass body.
Thick chrome plated brass ball.
PTFE seal.
Elastomer OR gaskets.
Threaded connections UNI-EN-ISO 228.
- Operating temperature with water 0 ÷ 80 °C

-  Ball bib-cock, with lever handle
-  *Robinet de distribution coudé à bille, avec poignée à levier*
-  *Шаровый кран с изогнутым сливом с ручкой-рычагом*
-  *Robinet de distribuție curbat cu bilă, cu manetă de tip levier*
-  *Grifo de jardín con palanca en aluminio, con toma para manguera*
-  *Gekrümmter Kugelhahn mit Hebelgriff*

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN	EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Кор. Ambalaj Embalaje Verpack.
2860.04.02	1/2"	10	-	8	64
2860.05.02	3/4"	10	-	6	48



052



2860

Ball bib-cock, with butterfly handle. Suitable for water, water+glycol.

Nickel plated brass body.
Thick chrome plated brass ball.
PTFE seal.
Elastomer OR gaskets.
Threaded connections UNI-EN-ISO 228.
- Operating temperature with water 0 ÷ 80 °C

-  Ball bib-cock, with butterfly handle
-  *Robinet de distribution coudé à bille, avec poignée papillon*
-  *Шаровый кран с изогнутым сливом с ручкой-бабочкой*
-  *Robinet de distribuție curbat cu bilă, cu manetă de tip fluture*
-  *Grifo de jardín con palomilla en aluminio, con toma para manguera*
-  *Gekrümmter Kugelhahn mit Flügelgriff*

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN	EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Кор. Ambalaj Embalaje Verpack.
2860.04.12	1/2"	10	-	10	80
2860.05.12	3/4"	10	-	8	64



052



3176

Angle ball valve, butterfly handle operated, F connection with M inlet coupling. Suitable for water, water + glycol.

Nickel plated brass body.
Thick chrome plated brass ball.
PTFE seal.
Elastomer OR gaskets.
Threaded connections UNI-EN-ISO 228.

- Operating temperature with water -20 ÷ 120 °C (without steam)



Angle ball valve, butterfly handle operated, F connection with M inlet coupling

Vanne à bille en équerre, actionnement par poignée papillon, raccord F avec manchon M

Шаровый клапан под прямым углом, с дроссельным приводом, крепление с внутренней резьбой со штуцером с внешней резьбой

Robinet cu bilă unghiular, acționare cu manetă fluture, prindere Mamă cu racord Tată

Válvula de esfera escuadra macho-hembra con racor 3 piezas, con palomilla en aluminio

Quadratisches Kugelventil, Betätigung mit Flügelgriff, Anschluss F mit M-Stutzen

Code Code Артикул Cod Código Code	Size Taille Размер Cod Dimensiunea Medida Abmessung	PN PN PN PN PN PN	EURO EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Кор. Ambalaj Embalaje Verpack.
3176.05.00	3/4"	25	-	5	40
3176.06.00	1"	25	-	4	32

052



3171

Three-way ball valve, T-shaped manoeuvre operated, with lever handle, FFF connections. Suitable for water, water+ glycol.

Nickel plated brass body.
Thick chrome plated brass ball.
PTFE seal.
Elastomer OR gaskets.
Threaded connections UNI-EN-ISO 228.

- Operating temperature with water -20 ÷ 120 °C (without steam)



Three-way ball valve, T-shaped manoeuvre operated, with lever handle, FFF connections

Vanne à bille à trois voies, actionnement par manoeuvre en T, avec poignée à levier, raccords FFF

Трехходовой шаровый кран Т-образный с ручкой-рычагом, вн.- вн. резьба

Supapă cu bilă cu trei canale, acționare cu manevră în T, cu manetă tip levier, prindere Mamă/Mamă/Mamă

Válvula de esfera 3 vías H-H-H, accionamiento a T, con palanca en aluminio, paso total, pesante

Drei-Wege-Kugelventil, Betätigung mit T-Bewegung, mit Hebelgriff, Anschlüsse FFF

Code Code Артикул Cod Código Code	Size Taille Размер Cod Dimensiunea Medida Abmessung	PN PN PN PN PN PN	EURO EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Кор. Ambalaj Embalaje Verpack.
3171.04.00	1/2"	25	-	1	6
3171.05.00	3/4"	25	-	1	6
3171.06.00	1"	25	-	1	6

052



3172

Three-way ball valve, L-shaped manoeuvre operated, with lever handle, FFF connections. Suitable for water, water+ glycol.

Nickel plated brass body.
Thick chrome plated brass ball.
PTFE seal.
Elastomer OR gaskets.
Threaded connections UNI-EN-ISO 228.

- Operating temperature with water -20 ÷ 120 °C (without steam)



Three-way ball valve, L-shaped manoeuvre operated, with lever handle, FFF connections

Vanne à bille à trois voies, actionnement par manoeuvre en L, avec poignée à levier, raccords FFF

Трехходовой шаровый кран L-образной с ручкой-рычагом, вн.- вн. резьба

Supapă cu bilă cu trei canale, acționare cu manevră în L, cu manetă tip levier, prindere Mamă/Mamă/Mamă

Válvula de esfera 3 vías H-H-H, accionamiento a L, con palanca en aluminio, paso total, pesante

Drei-Wege-Kugelventil, Betätigung mit L-Bewegung, mit Hebelgriff, Anschlüsse FFF

Code Code Артикул Cod Código Code	Size Taille Размер Cod Dimensiunea Medida Abmessung	PN PN PN PN PN PN	EURO EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Кор. Ambalaj Embalaje Verpack.
3172.04.00	1/2"	25	-	1	6
3172.05.00	3/4"	25	-	1	6
3172.06.00	1"	25	-	1	6

052



854

Standard bore ball valve, lever handle operated, FF connections. Suitable for water, water+glycol.

Nickel plated brass body.
Thick chrome plated brass ball.
PTFE seal.
Elastomer OR gaskets.
Threaded connections UNI-EN-ISO 228.

- Operating temperature with water -20 ÷ 120 °C (without steam)



- Standard bore ball valve, lever handle operated, FF connections
- Vanne à bille passage standard, actionnement par poignée à levier, raccords FF
- Шаровый кран стандартно-проходной с ручкой-рычагом, вн.- вн. резьба
- Supapă cu bilă cu trecere standard, cu acționare cu manetă tip levier, prinderi Mamă/Mamă
- Válvula de esfera hembra-hembra con palanca en aluminio, paso estándar
- Kugelventil Standarddurchfluss, Betätigung mit Hebelgriff, Anschlüsse FF

Code Code Articul Cod Codigo Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN	EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Коп. Ambalaj Embalaje Verpack.
855.03.32*	3/8"	50	-	20	80
854.04.32	1/2"	50	-	15	90
854.05.32	3/4"	50	-	12	48
854.06.32	1"	40	-	6	36
854.07.32	1"1/4	30	-	6	24
854.08.32	1"1/2	25	-	2	12
854.09.32	2"	25	-	2	8
3371 22N*	2"1/2	25	-	8	8
3371 30N*	3"	25	-	6	6
3371 40N*	4"	10	-	4	4

*Full bore



053

854

Standard bore ball valve, lever handle operated, FF connections. Suitable for water, water+glycol.

Nickel plated brass body.
Thick chrome plated brass ball.
PTFE seal.
Elastomer OR gaskets.
Threaded connections UNI-EN-ISO 228.

- Operating temperature with water -20 ÷ +120 °C (without steam)



- Standard bore ball valve, lever handle operated, FF connections
- Vanne à bille passage standard, actionnement par poignée à levier, raccords FF
- Шаровый кран стандартно-проходной с ручкой-рычагом, вн.- вн. резьба
- Supapă cu bilă cu trecere standard, cu acționare cu manetă tip levier, prinderi Mamă/Mamă
- Válvula de esfera hembra-hembra con palanca en aluminio, paso estándar
- Kugelventil Standarddurchfluss, Betätigung mit Hebelgriff, Anschlüsse FF

Code Code Articul Cod Codigo Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN	EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Коп. Ambalaj Embalaje Verpack.
855.03.42*	3/8"	50	-	20	80
854.04.42	1/2"	50	-	15	90
854.05.42	3/4"	50	-	12	48
854.06.42	1"	40	-	6	36
854.07.42	1"1/4	30	-	6	24
854.08.42	1"1/2	25	-	2	12
854.09.42	2"	25	-	2	8

*Full bore



053

989

Standard bore ball valve, butterfly handle operated, FF connections. Suitable for water, water+glycol.

Nickel plated brass body.
Thick chrome plated brass ball.
PTFE seal.
Elastomer OR gaskets.
Threaded connections UNI-EN-ISO 228.

- Operating temperature with water -20 ÷ 120 °C (without steam)



- Standard bore ball valve, butterfly handle operated, FF connections
- Vanne à bille passage standard, actionnement par poignée papillon, raccords FF
- Шаровый кран стандартно-проходной с ручкой-бабочкой, вн.- вн. резьба
- Supapă cu bilă cu trecere standard, cu acționare cu manetă tip fluture, prinderi Mamă/Mamă
- Válvula de esfera hembra-hembra con palomilla en aluminio, paso estándar
- Kugelventil Volldurchfluss für Gas mit Flügelgriff, Anschlüsse FF

Code Code Articul Cod Codigo Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN	EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Коп. Ambalaj Embalaje Verpack.
989.03.32*	3/8"	50	-	20	80
989.04.32	1/2"	50	-	15	90
989.05.32	3/4"	50	-	12	48
989.06.32	1"	40	-	6	36
989.07.32	1"1/4	30	-	8	24

*Full bore



053

885

Standard bore ball valve, lever handle operated, MM connections. Suitable for water, water+glycol.

Nickel plated brass body.
Thick chrome plated brass ball.
PTFE seal.
Elastomer OR gaskets.
Threaded connections UNI-EN-ISO 228.

- Operating temperature with water -20 ÷ 120 °C (without steam)



-  Standard bore ball valve, lever handle operated, MM connections
-  Vanne à bille passage standard, actionnement par poignée à levier, raccords MM
-  Шаровый кран стандартно-проходной с ручкой-рычагом, нар.- нар. резьба
-  Supapă cu bilă cu trecere standard, cu acționare cu manetă tip levier, prinderi Tată/Tată
-  Válvula de esfera macho-macho con palanca en aluminio, paso estándar
-  Kugelventil Volldurchfluss für Gas mit Hebelgriff, Anschlüsse MM

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN	EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Коп. Ambalaj Embalaje Verpack.
885.03.52*	3/8"	50	-	20	80
885.04.52	1/2"	50	-	15	60
885.05.52	3/4"	50	-	12	48
885.06.52	1"	40	-	6	36

*Full bore



053

885

Standard bore ball valve, lever handle operated, MM connections. Suitable for water, water+glycol.

Nickel plated brass body.
Thick chrome plated brass ball.
PTFE seal.
Elastomer OR gaskets.
Threaded connections UNI-EN-ISO 228.

- Operating temperature with water -20 ÷ +120 °C (without steam)



-  Standard bore ball valve, lever handle operated, MM connections
-  Vanne à bille passage standard, actionnement par poignée à levier, raccords MM
-  Шаровый кран стандартно-проходной с ручкой-рычагом, нар.- нар. резьба
-  Supapă cu bilă cu trecere standard, cu acționare cu manetă tip levier, prinderi Tată/Tată
-  Válvula de esfera macho-macho con palanca en aluminio, paso estándar
-  Kugelventil Volldurchfluss für Gas mit Hebelgriff, Anschlüsse MM

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN	EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Коп. Ambalaj Embalaje Verpack.
885.03.52*	3/8"	50	-	20	80
885.04.52	1/2"	50	-	15	60
885.05.52	3/4"	50	-	12	48
885.06.52	1"	40	-	6	36

*Full bore



053

885

Standard bore ball valve, butterfly handle operated, MM connections. Suitable for water, water+glycol.

Nickel plated brass body.
Thick chrome plated brass ball.
PTFE seal.
Elastomer OR gaskets.
Threaded connections UNI-EN-ISO 228.

- Operating temperature with water -20 ÷ 120 °C (without steam)



-  Standard bore ball valve, butterfly handle operated, MM connections
-  Vanne à bille passage standard, actionnement par poignée papillon, raccords MM
-  Шаровый кран стандартно-проходной с ручкой-бабочкой, нар.- нар. резьба
-  Supapă cu bilă cu trecere standard, cu acționare cu manetă tip fluture, prinderi Tată/Tată
-  Válvula de esfera macho-macho con palomilla en aluminio, paso estándar
-  Kugelventil Standarddurchfluss, Betätigung mit Flügelgriff, Anschlüsse MM

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN	EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Коп. Ambalaj Embalaje Verpack.
885.03.42*	3/8"	50	-	20	80
885.04.42	1/2"	50	-	15	60
885.05.42	3/4"	50	-	12	48
885.06.42	1"	40	-	6	36

*Full bore



053

886

Standard bore ball valve, lever handle operated, MF connections. Suitable for water, water+glycol.

Nickel plated brass body.
Thick chrome plated brass ball.
PTFE seal.
Elastomer OR gaskets.
Threaded connections UNI-EN-ISO 228.

- Operating temperature with water -20 ÷ 120 °C (without steam)



- Standard bore ball valve, lever handle operated, MF connections
- Vanne à bille passage standard, actionnement par poignée à levier, raccords MF
- Шаровый кран стандартно-проходной с ручкой-рычагом, нар.- вн. резьба
- Supapă cu bilă cu trecere standard, cu acționare cu manetă tip levier, prinderi Tată/Mamă
- Válvula de esfera macho-hembra con palanca en aluminio, paso estándar
- Kugelventil Standarddurchfluss, Betätigung mit Hebelgriff, Anschlüsse MF

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN	EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Коп. Ambalaj Embalaje Verpack.
886.03.32*	3/8"	50	-	1	40
886.04.32	1/2"	50	-	15	90
886.05.32	3/4"	50	-	12	48
886.06.32	1"	40	-	6	36
886.07.32	1"1/4	30	-	5	20
886.08.32	1"1/2	25	-	2	12
886.09.32	2"	25	-	2	8

*Full bore



053

886

Standard bore ball valve, lever handle operated, MF connections. Suitable for water, water+glycol.

Nickel plated brass body.
Thick chrome plated brass ball.
PTFE seal.
Elastomer OR gaskets.
Threaded connections UNI-EN-ISO 228.

- Operating temperature with water -20 ÷ +120 °C (without steam)



- Standard bore ball valve, lever handle operated, MF connections
- Vanne à bille passage standard, actionnement par poignée à levier, raccords MF
- Шаровый кран стандартно-проходной с ручкой-рычагом, нар.- вн. резьба
- Supapă cu bilă cu trecere standard, cu acționare cu manetă tip levier, prinderi Tată/Mamă
- Válvula de esfera macho-hembra con palanca en aluminio, paso estándar
- Kugelventil Standarddurchfluss, Betätigung mit Hebelgriff, Anschlüsse MF

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN	EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Коп. Ambalaj Embalaje Verpack.
886.03.42*	3/8"	50	-	20	80
886.04.42	1/2"	50	-	15	90
886.05.42	3/4"	50	-	12	48
886.06.42	1"	40	-	6	36
886.07.42	1"1/4	30	-	5	20
886.08.42	1"1/2	25	-	2	12
886.09.42	2"	25	-	2	8

*Full bore



053

887

Standard bore ball valve, butterfly handle operated, MF connections. Suitable for water, water+glycol.

Nickel plated brass body.
Thick chrome plated brass ball.
PTFE seal.
Elastomer OR gaskets.
Threaded connections UNI-EN-ISO 228.

- Operating temperature with water -20 ÷ 120 °C (without steam)



- Standard bore ball valve, butterfly handle operated, MF connections
- Vanne à bille passage standard, actionnement par poignée papillon, raccords MF
- Шаровый кран стандартно-проходной с ручкой-бабочкой, нар.- вн. резьба
- Supapă cu bilă cu trecere standard, cu acționare cu manetă tip fluture, prinderi Tată/Mamă
- Válvula de esfera macho-hembra con palomilla en aluminio, paso estándar
- Kugelventil Standarddurchfluss, Betätigung mit Flügelgriff, Anschlüsse MF

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN	EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Коп. Ambalaj Embalaje Verpack.
887.03.32*	3/8"	50	-	20	80
887.04.32	1/2"	50	-	15	90
887.05.32	3/4"	50	-	12	48
887.06.32	1"	40	-	6	36
887.07.32	1"1/4	30	-	6	18

*Full bore



053

67

Standard bore ball valve, butterfly handle operated, F connection with M inlet coupling. Suitable for water, water+glycol.

Nickel plated brass body.
Thick chrome plated brass ball.
PTFE seal.
Elastomer OR gaskets.
Threaded connections UNI-EN-ISO 228.

- Operating temperature with water $-20 \div 120$ °C
(without steam)



-  Standard bore ball valve, butterfly handle operated, MF connections
-  *Vanne à bille passage standard, actionnement par poignée papillon, raccords MF*
-  Шаровый кран стандартно-проходной с ручкой-бабочкой, нар.- вн. резьба
-  *Supapă cu bilă cu trecere standard, cu acționare cu manetă tip fluture, prinderi Tată/Mamă*
-  *Válvula de esfera macho-hembra con racor 3 piezas, palomilla roja en aluminio, paso estándar*
-  *Kugelventil Standarddurchfluss, Betätigung mit Flügelgriff, Anschluss F mit M-Stutzen*

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN	EURO EURO EURO EURO EURO	Pack Cond. Ynak. Cutie Caja Pack.	Carton Emballage Kop. Ambalaj Embalaje Verpack.
67.04.02	1/2" x 1/2"	25	-	20	80
67.05.02	3/4" x 3/4"	25	-	12	48
67.06.02	1" x 1"	25	-	6	24
67.07.02	1"1/4 x 1"1/4	25	-	4	16



053

67

Standard bore ball valve, butterfly handle operated, F connection with M inlet coupling. Suitable for water, water+glycol.

Nickel plated brass body.
Thick chrome plated brass ball.
PTFE seal.
Elastomer OR gaskets.
Threaded connections UNI-EN-ISO 228.

- Operating temperature with water $-20 \div 120$ °C
(without steam)



-  Standard bore ball valve, butterfly handle operated, F connection with M inlet coupling
-  *Vanne à bille passage standard, actionnement par poignée papillon, raccord F avec manchon M*
-  Шаровый кран стандартно-проходной с ручкой-бабочкой, нар.- вн. резьба
-  *Supapă cu bilă cu trecere standard, cu acționare cu manetă tip fluture, prinderi Mamă, cu ștuț tip Tată*
-  *Válvula de esfera macho-hembra con racor 3 piezas, palomilla azul en aluminio, paso estándar*
-  *Kugelventil Standarddurchfluss, Betätigung mit Flügelgriff, Anschluss F mit M-Stutzen*

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN	EURO EURO EURO EURO EURO	Pack Cond. Ynak. Cutie Caja Pack.	Carton Emballage Kop. Ambalaj Embalaje Verpack.
67.04.12	1/2" x 1/2"	25	-	20	80
67.05.12	3/4" x 3/4"	25	-	12	48
67.06.12	1" x 1"	25	-	6	24
67.07.12	1"1/4 x 1"1/4	25	-	4	16



053

2544

Standard bore ball valve, with built-in check valve, butterfly handle operated, pump connection 1"1/2. Suitable for water, water+glycol.

Nickel plated brass body.
Thick chrome plated brass ball.
PTFE seal.
VITON OR gaskets.
Threaded connections UNI-EN-ISO 228.

- Operating temperature with water -20 ÷ +120 °C
(without steam)

- Standard bore ball valve, with built-in check valve, butterfly handle operated, pump connection 1"1/2
- Vanne à boule à passage standard, avec clapet de retenue incorporé, actionnement avec poignée papillon, raccord pompe 1"1/2
- Шаровой клапан стандартного шага с запорным встроенным клапаном, управление с дроссельным регулятором, крепление для насоса 1"1/2
- Robinet cu bilă cu pasaj standard, cu supapă de reținere incorporată, acționare cu mâner fluture, racord pompă 1"1/2
- Válvula esférica de paso estándar, con válvula de retención incorporada, accionamiento con manija de mariposa, racor para bomba 1"1/2
- Kugelventil mit Standarddurchfluss, mit eingebautem Rückschlagventil, Betätigung mit Flügelgriff, Pumpenanschluss 1"1/2

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN PN	EURO EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Коп. Ambalaj Embalaje Verpack.
2544.05.00	3/4"x 1"1/2	50	-	4	24



Ball valve + built-in check valve.

2544

Standard bore ball valve, butterfly handle operated, pump connection 1"1/2. Suitable for water, water+glycol.

Nickel plated brass body.
Thick chrome plated brass ball.
PTFE seal.
VITON OR gaskets.
Threaded connections UNI-EN-ISO 228.

- Operating temperature with water -20 ÷ +120 °C
(without steam)

- Standard bore ball valve, butterfly handle operated, pump connection 1"1/2
- Vanne à boule à passage standard, actionnement avec poignée papillon, raccord pompe 1"1/2
- Шаровой клапан стандартного шага, управление с дроссельным регулятором, крепление для насоса 1"1/2
- Robinet cu bilă cu pasaj standard, acționare cu mâner fluture, racord pompă 1"1/2
- Válvula esférica de paso estándar, accionamiento con manija de mariposa, racor para bomba 1"1/2
- Kugelventil mit Standarddurchfluss, Betätigung mit Flügelgriff, Pumpenanschluss 1"1/2

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN PN	EURO EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Коп. Ambalaj Embalaje Verpack.
2544.05.10	3/4"x 1"1/2	50	-	4	24



2544

Standard bore ball valve, with built-in check valve, butterfly handle operated, pressure connection for copper pipe, pump connection 1"1/2. Suitable for water, water+glycol.

Nickel plated brass body.
Thick chrome plated brass ball.
PTFE seal.
VITON OR gaskets.
Threaded connections UNI-EN-ISO 228.
Copper pipe end connections.

- Operating temperature with water -20 ÷ +120 °C (without steam)



- Standard bore ball valve, with built-in check valve, butterfly handle operated, pressure connection for copper pipe, pump connection 1"1/2
- Vanne à boule à passage standard, avec clapet de retenue incorporé, actionnement avec poignée papillon, raccord à compression tube en cuivre et raccord pompe 1"1/2
- Шаровой клапан стандартного шага с запорным встроенным клапаном, управление с дроссельным регулятором, крепление с уплотнением для медной трубы и крепление для насоса 1"1/2
- Robinet cu bilă cu pasaj standard, cu supapă de reținere încorporată, acționare cu mâner fluture, racord cu compresie a tubului din cupru și racord pompă 1"1/2
- Válvula esférica de paso estándar, con válvula de retención incorporada, accionamiento con manija de mariposa, racor de compresión para tubo de cobre y racor para bomba 1"1/2
- Kugelventil mit Standarddurchfluss, mit eingebautem Rückschlagventil, Betätigung mit Flügelgriff, Klemmanschluss für Kupferrohr und Pumpenanschluss 1"1/2

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN	EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Кор. Ambalaj Embalaje Verpack.
2544.22.00	22 mm x 1"1/2	50	-	4	24

053



Ball valve + built-in check valve.

2544

Standard bore ball valve, butterfly handle operated, pressure connection for copper pipe, pump connection 1"1/2. Suitable for water, water+glycol.

Nickel plated brass body.
Thick chrome plated brass ball.
PTFE seal.
VITON OR gaskets.
Threaded connections UNI-EN-ISO 228.
Copper pipe end connections.

- Operating temperature with water -20 ÷ +120 °C (without steam)



- Standard bore ball valve, butterfly handle operated, pressure connection for copper pipe, pump connection 1"1/2
- Vanne à boule à passage standard, actionnement avec poignée papillon, raccord à compression tube en cuivre et raccord pompe 1"1/2
- Шаровой клапан стандартного шага, управление с дроссельным регулятором, крепление с уплотнением для медной трубы и крепление для насоса 1"1/2
- Robinet cu bilă cu pasaj standard, acționare cu mâner fluture, racord cu compresie a tubului din cupru și racord pompă 1"1/2
- Válvula esférica de paso estándar, accionamiento con manija de mariposa, racor de compresión para tubo de cobre y racor para bomba 1"1/2
- Kugelventil mit Standarddurchfluss, Betätigung mit Flügelgriff, Klemmanschluss für Kupferrohr und Pumpenanschluss 1"1/2

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN	EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Кор. Ambalaj Embalaje Verpack.
2544.22.10	22 mm x 1"1/2	50	-	4	24

053



2093

Standard bore ball valve, lever handle operated, copper pipe end connections. Suitable for water, water+glycol.

Nickel plated brass body.
Thick chrome plated brass ball.
PTFE seal.
Elastomer OR gaskets.
Copper pipe end connections.

- Operating temperature with water -20 ÷ +120 °C (without steam)



- Standard bore ball valve, lever handle operated, copper pipe end connections
- Vanne à bille à passage standard, réglage avec poignée levier, raccord à compression pour tube cuivre
- Шаровый кран стандартно-проходной с ручкой-рычагом, обжимное соединение для медных труб
- Robinet cu bila pasaj standard, actionare cu maneta, racorzi pentru teava de cupru
- Válvula de esfera con adaptadores para tubo de cobre y con palanca en aluminio, paso standar
- Kugelhahn, standard Durchfluss, mit Handgriff, Pressfitting für Kupferrohr

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN	EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Кор. Ambalaj Embalaje Verpack.
2093.15.20	15 mm	50	-	15	60
2093.22.20	22 mm	50	-	10	40
2093.28.20	28 mm	40	-	6	24
2093.35.20	35 mm	30	-	4	16
2093.42.20	42 mm	25	-	2	10
2093.54.20	54 mm	25	-	1	4



Iro®

053

2093

Standard bore ball valve, butterfly handle operated, copper pipe end connections. Suitable for water, water+glycol.

Nickel plated brass body.
Thick chrome plated brass ball.
PTFE seal.
Elastomer OR gaskets.
Copper pipe end connections.

- Operating temperature with water -20 ÷ +120 °C (without steam)



- Standard bore ball valve, butterfly handle operated, copper pipe end connections
- Vanne à bille à passage standard, réglage avec poignée papillon, raccord à compression pour tube cuivre
- Шаровый кран стандартно-проходной с ручкой-бабочкой, обжимное соединение для медных труб
- Robinet cu bila pasaj standard, actionare cu maneta fluture, racorzi pentru teava de cupru
- Válvula de esfera con adaptadores para tubo de cobre y con palomilla en aluminio, paso standar
- Kugelhahn, standard Durchfluss, mit Flügelgriff, Pressfitting für Kupferrohr

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN	EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Кор. Ambalaj Embalaje Verpack.
2093.15.00	15 mm	50	-	20	80
2093.22.00	22 mm	50	-	12	48
2093.28.00	28 mm	40	-	6	24
2093.35.00	35 mm	30	-	4	16



Iro®

053

3465

Standard bore ball valve, lever handle operated, FF connections. Suitable for water, water+glycol.

Nickel plated brass body.
Thick chrome plated brass ball.
PTFE seal.
Elastomer OR gaskets.
Threaded connections UNI-EN-ISO 228.

- Operating temperature with water 0 ÷ +80 °C



- Ball valve with standard flow, with water drain valve, lever handle operated, FF connections
- Vanne à bille à passage standard, avec vanne de vidange de l'eau, actionnement par poignée à levier, raccords FF
- Шаровый клапан стандартного шага со сливным клапаном воды, управление с дроссельным регулятором, крепления с ВНУП-ВНУП. резьбой
- Supapă cu bilă cu trecere standard, cu supapă de evacuare a apei, cu acționare cu manetă tip levier, prinderi Mamă/Mamă
- Válvula de esfera de paso estándar, con válvula de descarga de agua, accionamiento con palanca en aluminio, conexiones FF
- Kugelventil mit Standarddurchfluss, mit Wasserablassventil, Betätigung mit Hebelgriff, Anschlüsse FF

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN	EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Кор. Ambalaj Embalaje Verpack.
3465.04.00	1/2"	50	-	1	60
3465.05.00	3/4"	50	-	1	50
3465.06.00	1"	40	-	1	30



Iro®

053

3085

**Check valve, FF connections.
Suitable for water.**

Brass body.
Elastomer gaskets.
Threaded connections FF UNI-EN-ISO 228.

- Operating temperature with water 0 ÷ +80 °C



Check valve, FF connections, plastic rod

Clapet anti-retour, raccords FF, tige en plastique

Обратный клапан с пластиковым штоком, вн.-вн. резьба

Supapă de reținere, prinderi Mamă/Mamă, tija din plastic

Válvula antiretorno a disco, hembra-hembra, con eje en plástico

Rückschlagventil, Anschlüsse FF, Schaft aus Kunststoff

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN	EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Кор. Ambalaj Embalaje Verpack.
3085 38I	3/8"	16	-	10	120
3085 12I	1/2"	16	-	10	120
3085 34I	3/4"	16	-	10	120
3085 10I	1"	16	-	5	50
3085 04I	1"1/4	16	-	4	40
3085 02I	1"1/2	16	-	4	32
3085 20I	2"	16	-	2	20
3082 22	2"1/2	6	-	2	16
3082 30	3"	6	-	2	12
3082 40	4"	6	-	1	1

050



860

**Check valve, FF connections.
Suitable for water.**

Brass body.
Elastomer gaskets.
Stainless steel AISI 302 spring.
Threaded connections FF UNI-EN-ISO 228.

- Min. opening pressure 0.04 Bar
- Max operating temperature 90 °C (Water)
- Max operating temperature 110 °C (Air)



Check valve, FF connections, brass rod

Clapet anti-retour, raccords FF, tige en laiton

Обратный клапан с латунным штоком, вн.-вн. резьба

Supapă de reținere, prinderi Mamă/Mamă, tija din alamă

Válvula antiretorno a disco, hembra-hembra con eje en latón

Rückschlagventil, Anschlüsse FF, Schaft aus Messing

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN	EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Кор. Ambalaj Embalaje Verpack.
860.04.02	1/2"	25	-	30	120
860.05.02	3/4"	25	-	16	64
860.06.02	1"	25	-	10	60
860.07.02	1"1/4	16	-	8	32
860.08.02	1"1/2	16	-	4	24
860.09.02	2"	16	-	2	12

Check valve, FF connections, plastic rod

Clapet anti-retour, raccords FF, tige en plastique

Обратный клапан с пластиковым штоком, вн.-вн. резьба

Supapă de reținere, prinderi Mamă/Mamă, tija din plastic

Válvula antiretorno a disco, hembra-hembra con eje en plástico

Rückschlagventil, Anschlüsse FF, Schaft aus Kunststoff

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	PN PN PN PN PN	EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Кор. Ambalaj Embalaje Verpack.
860.04.12	1/2"	25	-	30	120
860.05.12	3/4"	25	-	16	64
860.06.12	1"	25	-	10	60
860.07.12	1"1/4	16	-	8	32
860.08.12	1"1/2	16	-	4	24
860.09.12	2"	16	-	2	12

054



3086

**Filter with threaded fitting.
Coupled with the check valves it forms a valid
protection for the pumps.**

Stainless steel AISI 304L filter.
Nylon 6.6 threaded fitting.
- Max operating temperature 90 °C



Stainless steel filter for check valves

Filtre en inox pour clapets anti-retour

Фильтр из нержавеющей стали для обратного клапана

Filtru de oțel inox pentru supape de reținere

Filtro en acero inox. para válvula antiretorno

Edelstahlfilter für Rückschlagventile

Code Code Артикул Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Кор. Ambalaj Embalaje Verpack.
3086 38I	3/8"	-	10	120
3086 12I	1/2"	-	10	120
3086 34I	3/4"	-	10	120
3086 10I	1"	-	10	100
3086 04I	1"1/4	-	8	80
3086 02I	1"1/2	-	8	64
3086 20I	2"	-	4	40
3086 22	2"1/2	-	3	-
3086 30	3"	-	2	-
3086 40	4"	-	1	8

050

20

Recessed stop cock with chrome plated cap.

Brass body.
Chromed cap and manoeuvring knob.
Elastomer seals.
threaded connections FF UNI-EN-ISO 228.

- Max operating temperature 110 °C
- Max operating pressure 10 Bar



- Built-in shut-off tap with chromed cap
- Robinet d'arrêt encastrable avec capuchon chromé
- Встраиваемый стопорный кран с хромированным колпаком
- Robinet de oprire cu încastrare cu capişon cromat
- Grifo de bloqueo empotrado con capucha cromada
- Einbausperhahn mit verchromter Kappe

Code Code Articul Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	Model Modèle Модель Model Modelo Modell	EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Kop. Ambalaj Embalaje Verpack.
20.04.00	1/2"	T	-	10	40
20.05.00	3/4"	T	-	5	40

053



30 mm extension for spacer fitting kit available. See spare parts pricelist. Product code 3516.00.02

589

Hydrant box with ball valve with hose connection. Suitable for water.

Brass valve body.
Thick chrome plated brass ball.
Polypropylene well.
PTFE valve seals.
Threaded connection UNI-EN-ISO 228.

- Operating temperature with water 0 ÷ +80 °C



- Hydrant box with ball valve with hose connection. Suitable for water
- Puisard pour arrosage avec robinet de fermeture à bille à raccord porte-caoutchouc
- Водяной гидрант в коробе с шаровым краном со штуцером для шланга
- Puț pentru irigare prevăzută cu hidrant de interceptare cu bilă cu prindere suport cauciuc
- Grifo de jardín empotrable en suelo, con caja y tapa, con toma para manguera
- Schacht für Bewässerung komplett mit Kugelabsperhhydrant mit Schlauchanschluss

Code Code Articul Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	Size Hose connection Dim. Porte-caoutchouc Диаметр шланга Dimens. Suport cauciuc Med. Toma manguera Abm. Schlauchanschluss	PN PN PN PN PN	EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Kop. Ambalaj Embalaje Verpack.
589.05.00	3/4"x3/4"	ø 15	16	-	1	10
589.06.00	3/4"x1"	ø 20	16	-	1	10

053

24

Wall siphon for washing machine.

Nickel brass body.
Stainless steel ceiling rose.
Hose connection Ø 22 mm.
Drain pipe connection Ø 32 mm.

- Max operating temperature 100 °C



- Wall siphon for washing machine
- Siphon mural pour machine à laver
- Сифон с настенным креплением для стиральной машины
- Sifon de perete pentru maşina de spălat
- Sifón de pared para lavarropas
- Wandsiphon für Waschmaschinen

Code Code Articul Cod Código Code	Size Taille Размер Dimensiunea Medida Abmessung	Model Modèle Модель Model Modelo Modell	EURO EURO EURO EURO EURO	Pack Cond. Упак. Cutie Caja Pack.	Carton Emballage Kop. Ambalaj Embalaje Verpack.
24.32.10	Ø 32	System	-	10	40

053